

HOUSINGS

Insulated Ceiling

- Compatible only with 4" Series
- Magnetic or electronic ballast
- Lamp wattage from 13W to 32W



New Construction

- 6", 7" and 8" Series with electronic ballast
- Vertical or horizontal lamp housings
- Emergency ballast available in horizontal lamp housings
- Lamp wattage from 13W to 42 W
- Available in 4" Series with magnetic or electronic ballast



Remodel

- 6", 7" and 8" Series with electronic ballast
- Vertical or horizontal bulbs
- Lamp wattage from 13W to 42 W
- Available in 4" Series with magnetic or electronic ballast



FEATURES

- Galvanized steel
- Listed for through branch wiring and damp location
- Keyhole on socket assembly for easier installation
- No light leak
- Perfect fit to ceiling
- Below ceiling accessible
- May be hung from trusses or suspended ceilings

Housings may differ from pictures.

When light becomes ART

CONTRAST
LIGHTING

Corporate Headquarters

1009, rue du Parc Industriel
Saint-Jean-Chrysostome
Québec, Canada G6Z 1C5
Phone : (418) 839-4624 Toll free : 1 888 839-4624
Fax : (418) 839-7057 Toll free : 1 877 839-7057

info@contrastlighting.com
www.contrastlighting.com



05-2009

Printed in Canada
© 2009 CONTRAST LIGHTING M.L. INC.
ALL RIGHTS RESERVED

CONTRAST
LIGHTING



Compact Fluorescent
Energy-Efficient Lighting

Compact Fluorescent Energy-Efficient Lighting

4", 6", 7" and 8" Series

Compact Fluorescent

4" Series



FB2675
DECOR
4 5/8"



FC2675
TRIM COLLAR
4 5/8"



A2000VL
FROSTED SMOOTH GLASS
4 1/4"

A2000VLS
FROSTED SMOOTH GLASS **SHOWER**
4 1/4"



A2401S
CONVEX **SHOWER**
4 1/4"



A2451S
LOW PROFILE CONVEX **SHOWER**
4 1/4"

6" Series



FR6HO & FR6VO
HORIZONTAL VERTICAL
OPEN
6 3/4"



FR6HOLA & FR6VOLA
HORIZONTAL VERTICAL
OPEN WITH LENS A
6 3/4"



FR6VOLB & FR6VOLB
HORIZONTAL VERTICAL
OPEN WITH LENS B
6 3/4"

BENEFITS

- Four times more efficient than the traditional incandescent light sources
- Average rated life: 10 000 hours
- Excellent color rendition
- Reduce energy cost
- Produce about 75% less heat
- Dimming capability with dedicated electronic ballast
- Adjustable beam in 6" vertical series
- Program start without flickering
- Available in 13 painted or plated finishes
- Wide selection of colors and wattages

7" & 8" Series



FR70 & FR80
OPEN (HORIZONTAL)
8" 9 1/4"



FR70LA & FR80LB
OPEN - LENS A (HORIZONTAL)
8" 9 1/4"



FR70LA & FR80LA
OPEN - LENS B (HORIZONTAL)
8" 9 1/4"



FR7C & FR8C
CROSS LOUVER (HORIZONTAL)
8" 9 1/4"



FR7T & FR8T
TURBO LOUVER
8" 9 1/4"