

ÉCLAIRAGE

P R I O R I

L I G H T I N G

COLLECTION COMMERCIALE ET RÉSIDENTIELLE

Garnitures 3 1/2" MR16 - GU10/GZ10

X3501-01



X3502-01



X3503-01



X3504-01



X3501-13



X3502-13



X3503-13



X3504-13



X3505-01



X3506-01



X3507-01



X3508-01




X3505-13



X3507-13



X3508-13



Pour le modèle X3506
l'étain satiné n'est
pas disponible.

COULEURS DE GARNITURES

	Code
Blanc	01
Blanc mat	11
Étain satiné	13

DIAMÈTRES EXTÉRIEURS

Garnitures	
3 1/2"	4"
Ø 4 7/8" [124 mm]	Ø 4 15/16" [125 mm]
Ø 4 7/16" [113 mm] (X3503)	
Ø 4 1/4" [108 mm] (X3502)	

BOÎTIERS

AMPOULES

	MR16	GU10/GZ10 or PAR20
Rénovateur		
Nouvelle construction		
Plafond isolé		

Garnitures 4" MR16 - GU10/GZ10

X4001-01



X4002-01



X4003-01



X4001-13



X4002-13



X4003-13



Garnitures 4" PAR20

X4004-01



X4004-13



X4005-01




X4005-13



Ampoules	BOÎTIERS POUR GARNITURES 3 1/2"			BOÎTIERS POUR GARNITURES 4"		
	Rénovateur	Nouvelle construction	Plafond isolé	Rénovateur	Nouvelle construction	Plafond isolé
MR16 50 W	XR35MR16M	XN35MR16M	XIC35MR16M	XR40MR16M	XN40MR16M	XIC40MR16
GU10/GZ10 50 W	XR35GU	XN35GU	XIC35GU	XR40GU	XN40GU	XIC40GU
PAR20 50 W	-	-	-	XR40PAR20	XN40PAR20	XIC40PAR20

RÉNOVATEUR

XR35MR16M (3 1/2")




INFORMATION TECHNIQUES

HAUTEUR DU POT: 4 1/2" (114 mm)
LARGEUR DU CADRE: 4 5/8" (117 mm)
LONGUEUR DU CADRE: 14 1/4 (362 mm)
120V/ 12v

TROU DE PERÇAGE

XR35: 3 5/8" (92 mm)

XR35GU (3 1/2")




INFORMATION TECHNIQUES

HAUTEUR DU POT: 4 1/2" (114 mm)
LARGEUR DU CADRE: 4 5/8" (117 mm)
LONGUEUR DU CADRE: 10 1/2 (267 mm)
120V

TROU DE PERÇAGE

XR35: 3 5/8" (92 mm)

XR40MR16M (4")




INFORMATION TECHNIQUES

HAUTEUR DU POT: 4 1/2" (114 mm)
LARGEUR DU CADRE: 5 1/4" (133 mm)
LONGUEUR DU CADRE: 14 1/2 (368 mm)
120V/ 12v

TROU DE PERÇAGE

XR40: 4 1/4" (107 mm)

XR40GU (4") XR40PAR20 (4")



INFORMATION TECHNIQUES



HAUTEUR DU POT: 5" (127 mm)
LARGEUR DU CADRE: 5 1/4" (133 mm)
LONGUEUR DU CADRE: 12" (305 mm)
120V

TROU DE PERÇAGE

XR40: 4 1/4" (107 mm)

NOUVELLE CONSTRUCTION

XN35MR16 (3 1/2") XN40MR16 (4")





INFORMATION TECHNIQUES

HAUTEUR DU POT: 5 3/8" (136 mm)
LARGEUR DU CADRE: 8" (203 mm)
LONGUEUR DU CADRE: 12 5/8 (321 mm)
120V/ 12V

TROU DE PERÇAGE

XN35: 3 5/8" (92 mm)
XN40: 4 1/4" (108 mm)

XN35GU (3 1/2") XN40GU (4") XN40PAR20 (4")



INFORMATION TECHNIQUES



HAUTEUR DU POT: 5 3/8" (136 mm)
LARGEUR DU CADRE: 6 1/2" (165 mm)
LONGUEUR DU CADRE: 9" (229 mm)
120V

TROU DE PERÇAGE

XN35: 3 5/8" (92 mm)
XN40: 4 1/4" (108 mm)

PLAFOND ISOLÉ

XIC35MR16M (3 1/2") XIC40MR16M (4")





INFORMATION TECHNIQUES

HAUTEUR DU POT: 5 3/8" (136 mm)
LARGEUR DU CADRE: 9 1/2" (241 mm)
LONGUEUR DU CADRE: 13 1/8 (333 mm)
120V/ 12v

TROU DE PERÇAGE

XIC35: 3 5/8" (92 mm)
XIC40: 4 1/4" (108 mm)

XIC35GU (3 1/2") XIC40GU (4") XIC40PAR20 (4")




INFORMATION TECHNIQUES

HAUTEUR DU POT: 5 3/8" (136 mm)
LARGEUR DU CADRE: 6 1/2" (165 mm)
LONGUEUR DU CADRE: 9" (229 mm)
120V

TROU DE PERÇAGE

XIC35: 3 5/8" (92 mm)
XIC40: 4 1/4" (108 mm)



Éclairage PRIORI

1009, rue du Parc Industriel
Saint-Jean-Chrysostome
Québec, Canada G6Z 1C5

Tél. : 1 888 839-4624
Fax : 1 877 839-7057