

NW3600CAU


3-1/2" PAR20 Series

New Construction Housing for PAR20 Lamp

SPECIFICATIONS

HOUSING DETAILS	18 gauge 0,051" (1,3 mm) thickness galvanized steel. Junction box can support up to 10 – 14 gauge wires or 8 – 12 gauge wires. Below-ceiling accessible.
SOCKET	Porcelain; medium base socket (E26). Pre-wired with 18 gauge wire SEW 200°C connected to the junction box.
MOUNTING	Cutout diameter: Ø 3-5/8" (92 mm) Can fit in ceilings up to 1-1/2" (38 mm) thick. Requires a 4" (103 mm) clearance beyond the ceiling material. Contraste hooks for ease of installation and a perfect fit to ceiling. Mounting bars extend from 10" (254 mm) to 24-1/2" (622 mm) to fit in most ceiling structures (compatible with suspended ceilings). No light leakage.
LIGHT SOURCE	PAR20 Halogen Lamp 50W MAX Although LED PAR20 works properly in this product, it may be longer than the halogen lamp it replaces. As a result, the lamp may protrude from the lighting fixture.
COMPATIBLE TRIMS	A3600 A3700 B3600
VOLTAGE	120 Volts (CAN & USA)
THERMAL PROTECTION	TC 248°F (120°C)
CERTIFICATION	cULus E174023 for damp locations
WARRANTY	5 years on socket

CODIFICATION EXAMPLE



ORDERING CODE

MODEL	SERIES	SOURCE	SOCKET
NW	3600	CA	U
NW New Construction Housing	3600 3-1/2" PAR20 Series	CA PAR20 Lamp	U Universal

Project _____

Notes _____

Fixture Type _____

Date _____

