

SPECIFICATION SHEET

T3450

3-1/2" Series – Coastal Line



Project _____

Notes _____



Fixture Type _____

Date _____

Low Profile Regressed Trim



T3450-11-QC (illustrated)
(Lamp not included)



SPECIFICATIONS

TRIM	Die-formed Stainless Steel. Different finishes available: Powder coat painted (Standard) White (-01), Black (-02), Matte White (-11) and Matte Black (-22)
LAMPS (not included)	GU10 LED 10W MAX MR16 GU5.3 37W MAX MR16 LED GU5.3 10W MAX If you want to use the dimming option and you use a LED lamp, please refer regularly to the lamp manufacturer compatibility list. For MR16 LED lamp usage, please refer to the selected housing specification sheet for details on transformer models (see compatible housing list below).
CEILING CUTOUT	ø 3-5/8" (92 mm)
ACCESSORIES	Goof Rings (see ordering code) Choice of optional lenses to customize your lighting: (see ordering codes) Clear (C): Frosted (F) Honeycomb (H): the honeycomb louver reduces glare Linear (L): the linear lens directs the lamps beam to create a strip of light Prismatic (P): the prismatic lens diffuses and spreads the light in an even overall pattern Solite (S): the solite lens softens the light in an even overall pattern Although not dangerous, the use of a 49 mm lens in conjunction with an LED lamp can result in overheating of the latter, reducing its lifespan. Contrast cannot be held responsible for the overheating of LED lamps used with accessory lenses.
CERTIFICATION	cULus for damp locations (for LED and halogens lamps)
WARRANTY	3-year limited warranty

